



Wasser-Rückkühler / Chiller  
Serie INCH midi

Die Wasser-Rückkühler Serie INCH midi besticht durch energieeffizientes Design und hohe Zuverlässigkeit. Standardmässig sind bereits ein Bypass im Flüssigkeitskreislauf sowie ein Hoch- und Niederdruckschalter im Kältekreislauf verbaut. Zusätzlich sind die Wasserkühler mit einem elektronischen Thermostat inklusive Sammelstörmeldung ausgestattet. Die Bauform der Serie INCH midi ermöglicht es auch leistungsstarke Geräte auf einer geringen Stellfläche zu platzieren.

The chiller series INCH midi impresses with energy-efficient design and a high reliability. A safety-bypass on the hydraulic circuit and high and low-pressure switches on the cooling circuit are built in as standard. Additionally the water chillers are equipped with an electronic thermostat including an anomaly signal. The design of the series INCH midi allows it to place units with high cooling power on a small utility area.



- Elektronischer Thermostat mit Störmeldekontakt
- Bypass zum Schutz der Pumpe
- Integrierter Tank
- Hoch- und Niederdruckschalter im Kältekreislauf
- Individuelle Ausstattung durch optionales Zubehör

- Electronic thermostat including anomaly signal
- Safety bypass to protect the pump
- Integrated tank
- High- and low-pressure switches
- Individual configuration by optional equipment

Serie INCH	Type Model	Tu Ta °C	Nutzkühlleistung Cooling Power W (W15L32)	Spannung Voltage V, Hz (Standard)	V, Hz (Optional)	Abmessungen B x H x T Dimensions W x H x D mm
Bestell-Nr./Order-No.						
20.INCH.0047.0122	FC-INCH-0047	45	4.700	400, 3~, 50	400/460, 3~, 50/60	560 x 1290 x 720
20.INCH.0059.0122	FC-INCH-0059	45	5.900	400, 3~, 50	400/460, 3~, 50/60	560 x 1290 x 720
20.INCH.0073.0122	FC-INCH-0073	45	7.300	400, 3~, 50	400/460, 3~, 50/60	560 x 1310 x 720
20.INCH.0087.0122	FC-INCH-0087	45	8.700	400, 3~, 50	400/460, 3~, 50/60	560 x 1310 x 720
20.INCH.0118.0122	FC-INCH-0118	45	11.800	400, 3~, 50	400/460, 3~, 50/60	740 x 1550 x 930
20.INCH.0137.0122	FC-INCH-0137	45	13.700	400, 3~, 50	400/460, 3~, 50/60	740 x 1550 x 930
20.INCH.0167.0122	FC-INCH-0167	45	16.700	400, 3~, 50	400/460, 3~, 50/60	740 x 1550 x 930
20.INCH.0189.0122	FC-INCH-0189	45	18.900	400, 3~, 50	400/460, 3~, 50/60	900 x 1992 x 1200
20.INCH.0241.0122	FC-INCH-0241	45	24.100	400, 3~, 50	400/460, 3~, 50/60	900 x 1992 x 1200
20.INCH.0293.0122	FC-INCH-0293	45	29.300	400, 3~, 50	400/460, 3~, 50/60	900 x 1992 x 1200
20.INCH.0330.0122	FC-INCH-0330	45	33.000	400, 3~, 50	400/460, 3~, 50/60	900 x 1992 x 1200
20.INCH.0412.0122	FC-INCH-0412	45	41.200	400, 3~, 50	400/460, 3~, 50/60	1140 x 2074 x 2084
20.INCH.0510.0122	FC-INCH-0510	45	51.000	400, 3~, 50	400/460, 3~, 50/60	1140 x 2074 x 2084

